

# **BAFFLE PLATE ASSEMBLY FOR A COMPRESSOR**

The application is a divisional application of an U.S.A. application with series No. 10/334,253, filed on December 30, 2002.

## **BACKGROUND OF THE INVENTION**

### **1. Field of the Invention**

The present invention relates to a baffle plate assembly, and more particularly to a baffle plate assembly for a compressor to guide the working fluid respectively into the compressing chamber and the motor chamber of the compressor in a certain proportion.

### **2. Description of Related Art**

To reduce the temperature in a compressor, part of a working fluid will be led into the motor chamber of the compressor to reduce the temperature of the motor. For example, US Patent 3,270,952 entitled "Protective Device For Compressors" to Bellmer shows a baffle plate mounted in a compressor and corresponding to the compressor inlet. Accordingly, the working fluid entering the compressor from the inlet will contact the baffle plate. Part of the working fluid will be led into the motor unit chamber to reduce the temperature of the motor, and the remaining working fluid will be led into the compressor unit chamber for the compressing process.

However, the baffle plate of Bellmer is a curved plate secured in the compressor, and the proportion of the working fluid flowing into the motor unit chamber and the compressor unit chamber is not certain. The compressor cannot work at an optimal condition due to the uncertain proportion of the working fluid used in this way. In addition, the working fluid entering from the inlet will impact the baffle plate of Bellmer directly at a high speed so as to make an undesirable noise.

To overcome the shortcomings, the present invention tends to provide a baffle

1 plate assembly to mitigate or obviate the aforementioned problems.

## 2 SUMMARY OF THE INVENTION

3 The main objective of the invention is to provide a baffle plate assembly for a  
4 compressor and that can lead the working fluid respectively into the compressing  
5 chamber and the motor chamber of the compressor in a certain proportion. The baffle  
6 plate assembly has a baffle plate comprising a back plate and a partition wall. The back  
7 plate has an inner space and is attached to the housing of the compressor. The partition  
8 wall is formed on the back plate to divide the inner space of the back plate into at least  
9 one upper guiding channel communicating with the compressing chamber in the  
10 compressor and at least one lower guiding channel communicating with the motor  
11 chamber of the compressor. Accordingly, the working fluid can be respectively led into  
12 the compressing chamber and the motor chamber of the compressor through the at least  
13 one upper guiding channel and the at least one lower guiding channel. Consequently, the  
14 compressor will operate at an optimal condition.

15 Other objects, advantages and novel features of the invention will become more  
16 apparent from the following detailed description when taken in conjunction with the  
17 accompanying drawings.

## 18 BRIEF DESCRIPTION OF THE DRAWINGS

19 Fig. 1 is a perspective view of a first embodiment of a baffle plate assembly in  
20 accordance with the present invention;

21 Fig. 2 is a side plan view in partial cross section of a compressor with a baffle  
22 plate assembly in Fig. 1;

23 Fig. 3 is a perspective view of a second embodiment of a baffle plate assembly  
24 in accordance with the present invention;

Fig. 4 is an enlarged cross sectional side plan view of part of a compressor with the baffle plate assembly in Fig. 3;

Fig. 5 is an enlarged cross sectional side plan view of part of a compressor with a third embodiment of a baffle plate assembly in accordance with the present invention;

Fig. 6 is a perspective view of a fourth embodiment of a baffle plate assembly in accordance with the present invention;

Fig. 7 is a cross section side plan view of the baffle plate assembly in Fig. 6 with a compressor showing the structural relationship between the baffle plate assembly and the inlet of the compressor;

Fig. 8 is a side plan view of part of a compressor with a fifth embodiment of a baffle plate assembly in accordance with the present invention;

Fig. 9 is a cross sectional side plan view of the compressor with the baffle plate assembly in Fig. 8; and

Fig. 10 is a perspective view in partial cross section of part of a compressor with a sixth embodiment of a baffle plate assembly in accordance with the present invention.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

With reference to Figs. 1 and 2, a baffle plate assembly for a compressor in accordance with the present invention comprises a baffle plate (10). The baffle plate (10) is attached to the housing of the compressor (50) at a position corresponding to the inlet (56) of the compressor (50). The baffle plate (10) has a back plate (12) and a partition wall (16). The back plate (10) has a U-shaped cross section to define an inner space in the back plate (10). Two wings (14) respectively extend from two sides of the back plate (10).

The partition wall (16) is formed on the back plate (12) to divide the inner space

1 of the back plate (12) into at least one upper guiding channel (17) and at least one lower  
2 guiding channel (18). In a first embodiment, the partition wall (16) is laterally formed  
3 between the wings (14) to divide the inner space into one upper guiding channel (17)  
4 above the partition wall (16) and one lower guiding channel (18) below the partition  
5 wall (16). Multiple recesses (122) are defined in the back plate (12) at a position  
6 corresponding to the upper guiding channel (17).

7 In another embodiment, the partition wall has a T shape to define one upper  
8 guiding channel (17) and two lower guiding channels (18) in the back plate (12), or the  
9 partition wall has an inverse T shape to define two upper guiding channels (17) and one  
10 lower guiding channel (18) in the back plate (12).

11 With reference to Figs. 1 and 2, the baffle plate (10) is securely attached to the  
12 housing of the compressor (50) at a position where the partition wall (16) faces the inlet  
13 (56) of the compressor (50). The inlet (56) simultaneously communicates with the upper  
14 guiding channel (17) and the lower guiding channel (18). In practice, screws (not shown)  
15 penetrate through the wings (14) on the back plate (12) and are screwed into the housing,  
16 such that the baffle plate (10) is securely attached to the housing with the screws. In  
17 another embodiment, the baffle plate is secured to the housing with a welding process.  
18 Accordingly, the upper guiding channel (17) and the lower guiding channel (18)  
19 simultaneously communicate with the inlet (56) and respectively communicate with the  
20 compressing chamber (52) and the motor chamber (54) in the compressor (50).

21 When the working fluid enters the housing from the inlet (56), the entering fluid  
22 will be divided and respectively led into compressing chamber (52) and the motor  
23 chamber (54) respectively through the upper guiding channel (17) and the lower guiding  
24 channel (18). The proportion of the fluid entering the compressing chamber (52) and the

1 motor chamber (54) is determined by the position where the partition wall (16) locates  
2 and is certain. The motor in the motor chamber (54) can be efficiently cooled by the  
3 working fluid entering into the motor chamber (54) in a certain proportion. The  
4 remaining working fluid entering into the compressing chamber (52) will also provide  
5 an excellent work effect for a refrigerating cycle or an air condition cycle. Therefore, the  
6 operation of the compressor (50) can be controlled under an optimal condition. In  
7 addition, the proportion of the fluid entering the compressing chamber (52) and the  
8 motor chamber (54) is adjustable by means of changing the location of the partition wall  
9 (16).

10 Additionally, the partition wall (16) can enhance the stiffness of the baffle plate  
11 (10) so as to reduce the noise when the working fluid impacts the baffle plate (10).

12 Furthermore, the recesses (122) in the back plate (12) can increase the area of  
13 the back plate (12) for the oil in the working fluid adhering to the back plate (12) when  
14 the working fluid passes through the upper guiding channel (17). This can keep the  
15 working fluid entering the compressing chamber (52) from containing too much oil, and  
16 the refrigerating effect provided by the working fluid is improved.

17 With reference to Figs. 3 and 4, in a second embodiment, a cavity (222) is  
18 defined in the back plate (22) at a position corresponding to the upper guiding channel  
19 (27) and above the lateral partition wall (26). Multiple recesses (224) are defined in the  
20 back plate (22) at a position corresponding to the cavity (222). With the arrangement of  
21 the cavity (222), the baffle plate (20) can fit with a compressor with a different structure,  
22 and the use of the baffle plate assembly is versatile. In an embodiment, the area on the  
23 back plate (22) corresponding to the cavity (222) has an inclined section. In another  
24 embodiment, with reference to Fig. 5, the area on the back plate (32) of the baffle plate

1 (30) corresponding to the cavity (322) has a curved cross section.

2 With reference to Figs.6 and 7, the partition wall (46) is longitudinally formed  
3 on the back plate (42) to divide the inner space into one upper guiding channel (47) and  
4 one lower guiding channel (48) respectively at two sides of the partition wall (46). A  
5 lower closed wall (462) extends from the bottom end of the partition wall (46) and is  
6 connected to the wing (44) corresponding to the upper guiding channel (47) to make an  
7 upper opening (not numbered) in the upper guiding channel (47). An upper closed wall  
8 (464) extends from the top end of the partition wall (46) and is connected to the other  
9 wing (44) corresponding to the lower guiding channel (48) to make a lower opening (not  
10 numbered) in the lower guiding channel (48).

11 Accordingly, the working fluid entering from the inlet (56) of the compressor  
12 will be led into the upper guiding channel (47) and the lower guiding channel (48) in a  
13 certain proportion and will be respectively discharged from the upper opening and the  
14 lower opening. In addition, multiple recesses (422) are defined in the back plate (42) of  
15 the baffle plate (40) at a position corresponding to the upper guiding channel (47) for the  
16 oil in the working fluid to adhere to the back plate (42).

17 With reference to Figs. 8 and 9, and in reference to Fig. 2, the baffle plate  
18 assembly further comprises a thermal-conductive element (19). The thermal conductive  
19 element (19) is attached to the bottom of the back plate (12) and is securely attached to  
20 the housing of the compressor (50). In practice, the thermal conductive element (19)  
21 comprises two metal plates combined with each other and each having a thermal  
22 expansion coefficient different from that of the other. The thermal conductive element  
23 will deform when the temperature in the motor chamber (54) changes.

24 The baffle plate (10) is moveably attached to the housing of the compressor (50)

1 and is attached to the thermal conductive element (19). A sliding device is mounted on  
2 the baffle plate (10) to make the baffle plate (10) be moveably attached to the housing of  
3 the compressor (50). In practice, the sliding device comprises two longitudinal grooves  
4 (142) respectively defined through the wings (14) and screws (not numbered)  
5 penetrating through the grooves (142). The screws penetrating through the grooves (142)  
6 are screwed into the housing of the compressor (50), such that the baffle plate (10) is  
7 moveably attached to the housing with the screws. In another embodiment, with  
8 reference to Fig. 10, the sliding device comprises two rails (15) each with a channel (152)  
9 respectively receiving the wings (14) in the channels (152), and the rails (15) are  
10 attached the housing. Consequently, the baffle plate (10) can move relative to the  
11 housing along the rails (15).

12           When the temperature in the motor chamber (54) rises, the thermal conductive  
13 element (19) deforms to push the baffle plate (10) to move upward. Accordingly, the  
14 area of the inlet (54) communicating with the lower guiding channel (18) is increased,  
15 such that the amount of the working fluid flowing into the motor chamber (54) will  
16 increase. This can provide an enhanced cooling effect to the motor in the motor chamber  
17 (54), and the temperature in the motor chamber (54) can be rapidly reduced.

18           When the temperature in the motor chamber (54) is reduced, the thermal  
19 conductive element (19) will deform to pull the baffle plate (10) to move downward.  
20 This can reduce the area in the inlet (56) communicating with the lower guiding channel  
21 (18), and the amount of the working fluid flowing into the motor chamber (54) is  
22 decreased. Accordingly, the temperature in the motor chamber (54) can be automatically  
23 controlled at a desired range by means of the movement of the baffle plate (10) actuated  
24 by the thermal conductive element (19). Consequently, the operation of the compressor

1 (50) is efficient and is improved.

2           Even though numerous characteristics and advantages of the present invention  
3 have been set forth in the foregoing description, together with details of the structure and  
4 function of the invention, the disclosure is illustrative only, and changes may be made in  
5 detail, especially in matters of shape, size, and arrangement of parts within the  
6 principles of the invention to the full extent indicated by the broad general meaning of  
7 the terms in which the appended claims are expressed.